



**Striker**<sup>™</sup>

**4x4**

An unrivaled combination of fire suppression, control, speed, and safety. Haul 5 firefighters at top speeds in the most comfortable ride ever – complete with a tighter turning radius, enormous storage compartments, exclusive Oshkosh<sup>®</sup> TAK-4<sup>®</sup> all-wheel independent suspension, and available Snozzle<sup>®</sup> HRET.

**OSHKOSH**  
AIRPORT  
PRODUCTS



**Striker**

# 4x4

FORWARD. FOREVER.

Take on ARFF hazards like never before. The Striker® 4x4 integrates single-source, severe-duty components that outperform anything else on the market.

#### UNMATCHED CHASSIS PERFORMANCE

- Exceeds NFPA, ICAO, FMVSS, and EU standards
- Oshkosh® patented TAK-4® all-wheel independent suspension
- Center steer for greater all-around visibility and control

#### INNOVATIVE FIRE SUPPRESSION

- Oshkosh® power divider allows for pump and roll in any condition
- Snozzle® HRET available
- Crosslays allow access to handlines from either side of the truck

#### SMART DESIGN

- Modular cab layout with switching and controls logically placed
- Spacious cab seats up to 5 firefighters
- Panoramic forward view
- Walk-in service ports with single-location filters
- Spacious storage compartments adapt to your needs
- Oshkosh® Command Zone™ allows simple diagnostic support

#### COMPLETE SUPPORT

- 24/7/365 global support
- Comprehensive parts/technical support at [airportproductsupport.com](http://airportproductsupport.com)
- Dedicated professional operators and maintenance training available



[oshkoshairport.com](http://oshkoshairport.com)



©2019 Oshkosh Corporation. Oshkosh, the Oshkosh logo, Snozzle, Striker and the Striker logo are registered trademarks and Command Zone is a trademark of Oshkosh Corporation. Oshkosh WI, USA, TAK-4 is a registered trademark of Oshkosh Defense, LLC, Oshkosh, WI. GA-0100-STWRH4MSUS 10/19

The Striker 4 x 4 meets or exceeds all National Fire Protection Association (NFPA) 414, Federal Aviation Administration (FAA) and International Civil Aviation Organization (ICAO) requirements for all 1,500-gallon (5,678-liter) water capacity ARFF vehicles.